

## atn802 White

## NYLON/POLYESTER blend taffeta

- Printable both sides
- Roll up resistant after washing
- Coated both sides

**ATN802** provides highly accurate printing at a competitive price level compared to other printable fabrics materials. The coating allows it to be printable using Thermal Transfer technology and remain flat after washing cycles.

Selected for optimal compatibility with **AXR®TX** Thermal Transfer Ribbon.

### POLYESTER

> **atp811** white  
Dyeing process resistant

> **atp812** white  
Dyeing process resistant

### SATIN

> **ats821** white  
Anti-fray

> **ats811** white  
Dyeing/Tanning/Stonewashing...

> **ats612** white  
Recycled yarns

> **ats602** white

> **ats601** white

### NYLON

> **atn802** white  
Roll up resistant

> **atn602** white

> **atn501** white

Printable 1 side only

Printable both sides

### Resistances

**Washing**  
AATCC61-2A

**Ironing**

Stone washing

Tanning

Enzyme washing


**Dry cleaning**

Dyeing process

Anti-fray

### Fabric specifications

- Color:** white
- Density:**
  - Warp: 43 yarns/cm
  - Weft: 22 yarns/cm
- Total weight: 70 g/m<sup>2</sup>**
  - Coating weight 16 g/m<sup>2</sup>
  - Fabric weight 54 g/m<sup>2</sup>
- Thickness:** < 0,125mm



### Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
- Roll width:** min 20 mm, max 220 mm
- Roll length:** min 50 m, max 400 m

Refer to the offer brochure for more information

### Certifications

- REACH / SVHC 1907/2006/EC**



### Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)