



ATS601 White

- Printable 1 side (outside)
- Cost efficient
- Uncoated

Satin Polyester is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel.

The calendaring of **ATS601** allows it to be printed on the outside.

Selected for optimal compatibility with **AXR[®]TX** Thermal Transfer Ribbon.

Resistances

- | | |
|------------------------------|---------------------|
| Washing
AATCC61-2A | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Fabric specifications



- Color:** white
- Density:**
 - Warp: 120 yarns/cm
 - Weft: 41 yarns/cm
- Total weight: 106 g/m²**
 - Fabric weight 106 g/m²
 - This fabric is uncoated
- Thickness:** < 0,110mm

100% SATIN POLYESTER

POLYESTER	
> ATP811 white Dyeing process resistant	> ATP812 white Dyeing process resistant
SATIN	
> ATS821 white Anti-fray	> ATS612 white Recycled yarns > ATS602 white
> ATS811 white Dyeing/Tanning/Stonewashing...	
> ATS601 white	
NYLON	
> ATN501 white	> ATN802 white Roll up resistant > ATN602 white

Printable 1 side only **Printable both sides**

Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
 - Roll width:** min 20 mm, max 220 mm
 - Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information*

Certifications

- REACH / SVHC 1907/2006/EC**



Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)