



## ATS612 White

- Printable both sides
- Recycled yarns
- Uncoated

**Satin Polyester** is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel.

**ATS612** is made of recycled yarns.

Selected for optimal compatibility with **AXR®TX** Thermal Transfer Ribbon.

## 100% SATIN POLYESTER

### POLYESTER

> **ATP811** white  
Dyeing process resistant

> **ATP812** white  
Dyeing process resistant

### SATIN

> **ATS821** white  
Anti-fray

> **ATS811** white  
Dyeing/Tanning/Stonewashing...

> **ATS612** white  
Recycled yarns

> **ATS602** white

> **ATS601** white

### NYLON

> **ATN501** white

> **ATN802** white  
Roll up resistant

> **ATN602** white

Printable 1 side only

Printable both sides

### Resistances

**Washing**  
AATCC61-2A

**Ironing**

Stone washing

Tanning

Enzyme washing

**Dry cleaning**

Dyeing process

Anti-fray

### Roll specifications

- **Core diameter:** 1", 1,5", 2", 3"
- **Roll width:** min 20 mm, max 220 mm
- **Roll length:** min 50 m, max 400 m

Refer to the offer brochure for more information

### Certifications

- **REACH / SVHC** 1907/2006/EC



### Fabric specifications



- **Color:** white
- **Density:**
  - Warp: 118 yarns/cm
  - Weft: 38 yarns/cm
- **Total weight: 140 g/m<sup>2</sup>**
  - Fabric weight 140 g/m<sup>2</sup>
  - This fabric is uncoated
- **Thickness:** < 0,135mm
- **Recycled yarns**

### Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)