



## ATS811 White

- Printable 1 side (outside)
- Resistant to several industrial processes
- Coated both sides

**Satin Polyester** is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. The coating of **ATS811** allows it to resist to several garment/leather processes such as stone washing, enzyme washing, tanning, dyeing process and anti-fray.

Selected for optimal compatibility with **AXR<sup>®</sup>TX** Thermal Transfer Ribbon.

### Resistances

- |                              |                     |
|------------------------------|---------------------|
| <b>Washing</b><br>AATCC61-2A | <b>Ironing</b>      |
| <b>Stone washing</b>         | <b>Tanning</b>      |
| <b>Enzyme washing</b>        | <b>Dry cleaning</b> |
| <b>Dyeing process</b>        | <b>Anti-fray</b>    |

### Fabric specifications



- Color:** white
- Density:**
  - Warp: 120 yarns/cm
  - Weft: 40 yarns/cm
- Total weight: 108 g/m<sup>2</sup>**
  - Coating weight 3 g/m<sup>2</sup>
  - Fabric weight 105 g/m<sup>2</sup>
- Thickness:** < 0,115mm

## 100% SATIN POLYESTER

### POLYESTER

- > **ATP811** white  
Dyeing process resistant
- > **ATP812** white  
Dyeing process resistant

### SATIN

- > **ATS821** white  
Anti-fray
- > **ATS811** white  
Dyeing/Tanning/Stonewashing...
- > **ATS612** white  
Recycled yarns
- > **ATS602** white
- > **ATS601** white

### NYLON

- > **ATN802** white  
Roll up resistant
- > **ATN602** white
- > **ATN501** white

Printable 1 side only

Printable both sides

### Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
  - Roll width:** min 20 mm, max 220 mm
  - Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information

### Certifications

- REACH / SVHC 1907/2006/EC



### Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)